

ESD Table Mat



Size	Length: 10m, Thickness: 2mm, Width: 600, 1000mm	
Material	Rubber	
Unit	Specification	
Hardness (KSM 6518-19)	Top Layer	65
	Bottom Layer	65
Tensile Strength (kg/mm ²)	Top Layer	114
	Bottom Layer	112
Elongation (%)	Top Layer	370
	Bottom Layer	380
Surface Resistivity (ASTM D257)	Top Layer	10E7 – 10E8 Ω/SQ
	Bottom Layer	10E4 – 10E5 Ω/SQ
Static Decay 5KV – 0KV	Less than 0.1 second	
Resistance to Ground	Less than 10E8 Ω	
Chemical Resistance	Resistant to Solvent, Acid, Alkali, Oil and Aromatics	
	Not resistant to Ketone and DOP	

Part No.	Description
CNRMSGN60	ESD Table Mat, Shiny Green, 60cm x 10m
CNRMSGN100	ESD Table Mat, Shiny Green, 100cm x 10m
CNRMSGY60	ESD Table Mat, Shiny Grey, 60cm x 10m
CNRMDBN60	ESD Table Mat, Dull Brown, 60cm x 10m
CNRMDBN100	ESD Table Mat, Dull Brown, 100cm x 10m
CNRMSBL100	ESD Table Mat, Shiny Blue, 100cm x 10m

Anti-Fatigue Mat



Tough, long lasting static dissipative anti-fatigue matting providing comfort underfoot. Surface resistivity is 10E6 – 10E9 ohms/sq and should be used in conjunction with grounded flooring

Part No.	Description
AFL	Bondline Anti-Fatigue Matting 0.9 x 10.3m

Grounding Cord

Table Mat Grounding Cord

Grounds Table and Floor Mat with preinstalled 10mm male snap fastener. Available in 6ft and 15ft Length. Mould dome cap reduces tripping. Ring terminal or Banana Plug with Crocodile Clip. 1 mega-ohm resistor



Wrist Strap Grounding Cord

Mounted on workstation allows two operators to ground their Wrist Strap.



Part No.	Description
GC15	Table Mat Grounding Cord, 15ft
TWC2	Wrist Strap Grounding Cord

Surface Resistivity / Resistance Checker



This unique Surface Resistivity Meter is extremely accurate and indicates resistance to “half a decade” through the important static-dissipative range using 10/100 volt test voltages to ensure more accurate readings

Part No.	Description
SRM100	Bondline Surface Resistivity Checker